



Concealed hinge, Häfele Metallamat A/SM 175°, full overlay mounting

For screw fixing, drilling pattern 48/6, A slide-on system

Art. no. 316.32.600

Article details

Area of application	for cabinets with internal pull outs or extending trays
Function	With automatic closing spring
Concealed hinge version	full overlay
Crank type	Straight
For door material	Wood
Door processing for assembly	with cup drilling
Product Material	Cup: Zinc alloy, Hinge arm: Steel
Colour/finish	nickel plated
Opening angle	175°
Cup drilling depth	12.50 mm
Cup drilling Ø	35.00 mm
Cup fixing	for screw fixing
Drilling pattern	48/6
Adjustment facility	3-dimensional (with appropriate mounting plate)
Installation	Door on cabinet with slide-on system A



Technical data attributes

Door thickness mm	Distance to cup E mm					
	3,0	4,0	5,0	6,0	7,0	8,0
	20–24	keine Fuge notwendig	keine Fuge notwendig	keine Fuge notwendig	keine Fuge notwendig	keine Fuge notwendig
	25	3,2	3,0	2,7	2,1	1,6
26	6,0	5,2	4,4	3,6	2,8	2,0
Minimum gap F						

Door overlay mm													
11	12	13	14	15	16	17	18	19	20	21	22	A	SM
						3	4	5	6	7	8	2	
					3	4	5	6	7	8			3
				3	4	5	6	7	8			4	4
		3	4	5	6	7	8					6	6
3	4	5	6	7	8							8	8
Distance to cup E mm							Mounting plate distance mm						

Mounting plates are available for slide-on system (A) with 2, 4, 6 and 8 mm, for quick fixing system (SM) with 3, 4, 6 and 8 mm.

Additional information attributes

The dimensions and gap specifications in the drawings and tables are calculated:
with factory settings
with mounting plate distance 0 mm

