



Concealed hinge, Häfele Metallamat A 92°, for -45° corner application

Art. no. 316.39.501

Clearance

Article details

Area of application	for corner applications
Function	With automatic closing spring
Concealed hinge version	blind corner application
Crank type	Cranked
For door material	wood
Door processing for assembly	with cup drilling
Product Material	Cup: Steel, Hinge arm: Zinc alloy
Colour/finish	nickel plated
Opening angle	92°
Corner applications	45°
Cup drilling depth	12.5 mm
Cup fixing	for screw fixing
Drilling pattern	48/6
Adjustment facility	3-dimensional (with appropriate mounting plate)
Installation	Door on cabinet with slide-on system A



Technical data attributes

Door thickness mm	Distance to cup E mm				
	3,0	4,0	5,0	6,0	7,0
15	0,6	0,6	0,6	0,6	0,6
16	0,8	0,8	0,8	0,8	0,8
17	1,1	1,0	1,0	1,0	1,0
18	1,4	1,4	1,3	1,3	1,3
19	1,8	1,7	1,7	1,6	1,6
20	2,2	2,1	2,0	2,0	2,0
21	2,8	2,6	2,5	2,4	2,3
22	3,4	3,1	3,0	2,8	2,7
23	4,1	3,8	3,6	3,3	3,2
24	4,9	4,5	4,2	4,0	3,8
25	5,8	5,3	4,9	4,6	4,3
26	6,6	6,2	5,7	5,3	5,1
Minimum gap F					

Additional information attributes

The dimensions and gap specifications of the drawings and tables are calculated:
with factory settings
With mounting plate distance 0 mm

