





Wardrobe rail, Häfele Dresscode profile 5104 for LED strip lights 8 mm

straight-edged

Product details

Can be freely positioned in the 32 mm interval system Easy installation without tools Concealed fixing

Application	Illuminated wardrobe rail
Version	Can be cut to required size Can be combined with LED strip lights
Product Material	Profile: Diffuser:
Installation note	Can be freely positioned at intervals of 32 mm Easy installation without tools Concealed fixing Can be combined with Häfele Loox LED strip lights

Order reference

Please order Loox strip lights, drivers and switches separately.

Supplied with

- 1 aluminium profile
- 1 diffuser

Additional information attributes


For LED strip lights up to 8 mm wide.

The surface that is to be bonded must always be cleaned before bonding to the LED strip lights. It must be completely clean, grease-free and dust-free!

Load bearing capacity: 40 kg with wardrobe rail 1,000 mm and Dresscode rail end support in accordance with DIN 68890:2009

Print date:03-Jul-2025

Installation drawings



Article table (4)		
straight-edged, umber grey, RAL 7022, 1200 mm	Art. no. 801.26.501	
straight-edged, umber grey, RAL 7022, 2500 mm	Art. no. 801.26.502	
straight-edged, traffic white, RAL 9016, 1200 mm	Art. no. 801.26.701	
straight-edged, traffic white, RAL 9016, 2500 mm	Art. no. 801.26.702	

Print date:03-Jul-2025